

LATCO ENGINEERING ROLL-UP ACTION HIGH SPEED DOOR – GENERAL

The LATCO Engineering Roll-Up Action High Speed Door is an energy saving door with roll-up action ideally suited for internal use. Its compact design, thanks to its fully integrated curtain, is the answer to the problem of limited space and it can be installed with the minimum of disruption and site preparation making it the ideal choice for separating internal areas. It is designed for high traffic flows, low cost maintenance and trouble free operation with many hundreds of models in daily operation. For external use we offer a fold-up action High Speed Door.

Standards: The door meets or exceeds the requirements of BS EN 12604:2000 Industrial, commercial and garage doors and gates – Mechanical aspects – Requirements; BS EN 12453:2001 Industrial, commercial and garage doors and gates – Safety in use of power operated doors – Requirements and BS EN12978:2003 Industrial, commercial and garage doors – Safety devices for power operated doors and gates – Requirements and test methods, and is CE marked when fully installed.

Opening Activation: To activate door opening the following methods can be used individually or in parallel: induction floor loops; photo-electric cells; radar; hand-held or vehicle mounted transmitters; push button (single, double or mushroom); pull cord. Where pedestrian access is permitted or unavoidable please consult us for advice on stand-off sensing devices or alternative methods of protection.

Frame: Self supporting 2.5mm mill galvanized steel frame with epoxy powder coated finish in a choice of ten standard colours and limitless non-standard colours. The curtain assemblies are made from mechanically welded 4.0mm steel. The frame is positioned directly to the wall and fixed to the floor.

Drive Unit: The highly rated in line geared electric motor with brake drive provides a reliable standard operation with 1m/s opening and 0.5m/s closing speed. The time delay before closing can be varied to suit your requirements. A hollow shaft greased for life is coupled directly to the motor. Power is 0.37 to 0.55kW, 230v or 400v three phase with IP55 protection. The brake engages in case of power failure.

Curtain: The fabric is a multi-layered high frequency welded PVC and polyester 900g/m² screen, anti UV and saline solution treated, ensuring very high tear resistance and long life. The fabric is available in a choice of ten standard colours and limitless non-standard colours. Optional vision panels are available.

Draught Sealing: The uprights are sealed by a double row of side brushes which reduce the play between the curtain and the guide and provide an excellent sound barrier. A flexible flap at the bottom of the apron provides the best possible match to an uneven floor surface.

Multi Safety Devices: Jamb-mounted dual safety electro-sensitive photocells constantly monitor to insure safe operation. This prevents the curtain closing if a person has entered the opening. Should the beam be broken during the closing cycle the curtain will be fully raised. Two warning lights flash when the door operates. Multiple horizontal strengtheners eliminate the need for a troublesome and expensive bottom bar.

Colour Choices: Standard colours for the frame and curtain are White, Sky Blue, Royal Blue, Cream, Yellow, Dark Green, Grey, Orange, Brown, Red and Black. Non-standard colours are limitless.

Installation: LATCO Engineering Limited will undertake full preparation, installation, wiring, commissioning and staff training as well as any required in-fills/flashings.

Warranty: We warrant all parts free from manufacturer's defects for a period of twelve months from the commissioning date. The warranty also covers call out charges and fitting charges for replacement parts supplied under the warranty. The warranty does not cover repairs due to accidental damage or misuse, fair wear and tear or any loss of use while replacement parts are being supplied or fitted.

Maintenance: Most doors are subjected to a certain amount of abuse and everyday wear and therefore it is advisable to identify and correct any faults at an early stage. This ensures trouble free operation and avoids potentially costly repair damage. In accordance with the Supply of Machinery (Safety) Regulations 1992, it is a requirement that the end user of all industrial doors establish a fully documented maintenance regime in accordance with the manufacturer's recommendations. Failure to do so may result in prosecution in the event of an accident.

Our Planned Maintenance can help you fulfil your legal requirements and ensure that Health and Safety obligations are met. We will recommend a maintenance programme for your doors relevant to their application, usage, duty, speed of operation and any other relevant local condition.

Service Support: Accidents happen and breakdowns occur – it's an undeniable fact of working life, and ensuring that the support is there when required gives peace of mind that down-time will be kept to a minimum. LATCO Engineering's technicians are on 24 hour call for such an eventuality. The product is British made and all components are sourced locally to ensure that any replacement part costs and delays are kept to a minimum.

Actuation Methods

A selection of actuation options are available as shown in illustrations below.

